



## M16 Clear Polypropylene with Cold Temperature Permanent Adhesive

### Facestock Description

A biaxially oriented clear polypropylene film with good stiffness and flatness properties optimized and engineered to run specifically on HP Indigo Digital Printing Systems.

Test Property .....	Typical Values
Type.....	Clear Polypropylene
Basis Weight (lbs.).....	N/A
Caliper (mils) .....	2.0

### Adhesive Description

PCT-2242, a cold temperature emulsion acrylic permanent which exhibits moderate initial tack to a variety of substrates. Adhesion to rigid plastics, film, glass and painted metals is good. Complies with FDA 175.105 standards for indirect food contact.

Test Property .....	Typical Values
Type.....	Cold Temperature Permanent
Application Temperature (Minimum) .....	+35°F
Service Temperature Range .....	-10°F to +200°F

### Liner Description

Test Property .....	Typical Values
Type.....	Clear Polyester Film
Caliper (mils) .....	1.2

As with all pressure-sensitive materials, LABELTRONIX® recommends this product be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

***\*Please note that the above data represents expected averages with variances following industry standards. They should not be misinterpreted as minimum or absolute values. As the products are used outside our control, we cannot take responsibility for any damage which may be caused using the product.***

This specification sheet was updated and confirmed as of 07/11/08.